



QMFZ2 Component - Plastics

Friday, October 24, 2003

E54688

**BOLTARON PERFORMANCE PRODUCTS L L C**  
 1 GENERAL ST NEWCOMERSTOWN OH 43832

Material Designation: **6540**

Product Description: Acrylonitrile Butadiene Styrene/Polyvinylchloride (ABS/PVC), designated "Boltaron" furnished as sheets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.2	V-0, 5VB	-	-	50	50	50	-	-
ALL	3.4	V-0, 5VA	-	-	50	50	50	-	-

CTI: - IEC CTI (V): - HVTR: - D495: - IEC Ball Pressure (°C): -  
 Dielectric Strength (kV/mm): - Volume Resistivity (10<sup>x</sup>ohm-cm): - Dimensional Stability(%): -  
 ISO Tensile Strength (MPa): - ISO Flexural Strength (MPa): - ISO Heat Deflection (°C): -  
 ISO Tensile Impact (kJ/m<sup>2</sup>): - ISO Izod Impact (kJ/m<sup>2</sup>): - ISO Charpy Impact (kJ/m<sup>2</sup>): -

Report Date: 2/22/2001

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.